


Hydraulic principle diagram



Main specification of winch

额定起升能力 / 力 Rated lifting capacity / force	14
绳径 / mm Rope diameter	20
额定绳速 / m/min Rated rope speed	18
总容量 / m³ Total displacement	1663.2
额定容量 / m³ Rated capacity	200
绳径 / mm Rope diameter	14
绳层数 / 层 Layers of rope	8
额定绳速 / m/min Rated rope speed	38 (η=0.92)
液压马达型号 Hydraulic motor model	A2FM63
箱体型号 Gearbox model	FFT09W2-B26.4
制动器额定扭矩 / kN·m Rated torque of brake	450
制动器额定速度 / r/min Rated speed of brake	2-2.5

10	GB/T 70.1-2000	6020372.0	socket head cap screw M16x40	16	12.9 grade		3700236
9	GB/T 70.1-2000	6020213.0	socket head cap screw M10x30	4	12.9grade		3700033
8	A2FM63/61WVAB010	6160112.0	hydraulic motor	1			
7	FJ07-30-80-13-ZP-2K100-5	3071131.0	rope pressing plate	2	ZG350		4400191
6	FJ2-5-20-65-12-ZP-FGM05-3	3030664.0	right support shaft	1	QT500-7		4300077
5	FJ09-23-200-14-ZP-3	14060106.0	external brake band assembly	1			
4	3190340.0	F0833-200-14-ZP-3	drum	1	Q345B		
3	FFT09T2-B26.4-6800-A61M63	14030084.0	gearbox assembly	1			
2	FJ09-23-200-14-ZP-1	3190339.0	frame	1	Q345B		
1	F602011-A2FM63-G1/2	11140053.0	manifold block system	1			

序号	图号	物料编码	名称	数量	材料	单件重量	总计重量	备注
<p>Assembling drawing</p> <p>宁波弗莱格传动有限公司 Ningbo Flag-up transmission Co.,Ltd</p> <p>hydraulic winch</p> <p>FJ09-23-200-14-ZP</p> <p>1:3.5</p> <p>2025-04-09</p>								

16	FJ09-23-200-14-ZP-4	3201258.0	protective cover	1	Q235B			
15	GB/T 70.1-2000	6020180.0	socket head cap screw M10x35	4	12.9grade		3700001	
14	GB/T 70.1-2000	6020249.0	socket head cap screw M10x25	7	12.9grade		37000071	
13	GB/T 894.1-1986	6040024.0	shaft retaining ring 55x2	1	65Mn		3600040	
12	GB/T 276-1994	6050085.0	groove ball bearing 6211-2Z	1	55x100x21		3200027	
11	GB/T 5782	6020396.0	external hex bolt M10x30	20	12.9grade		3700262	

借通用件登记

插图

缺番

图号

签字

日期